



pitch	7 mm
Height	7.25 mm
Depth	9.2 mm
Dimensional class	Alta
Wire section	-
Clamp opening size	-
Wire stripping	-
Operating temperature	-40 ÷ +130 °C

Current	11 A
Voltage	500 V
Test Voltage	6 kVrms/60s

Screw	-
Recommended torque	-



		EN 61984	UL 1059
Current	-	11 A	11 A factory / 11 A field
Voltage	-	400 V	300 V
Wire section	-	-	-
Torque	-	-	-
FILE	-	40048261	E178356

Housing	PA - UL 94 V0
Screw	-
Clamp	-
Terminal	Tin-plated copper alloy
SCIP Number	892ed63d-670d-4367-9365-34dfcaff593c

Standard	On request
----------	------------



POLES	NAME	3D FILE
02	PV02-7-H-K	File not available for this product
03	PV03-7-H-K	File not available for this product
04	PV04-7-H-K	File not available for this product
05	PV05-7-H-K	File not available for this product
06	PV06-7-H-K	File not available for this product
07	PV07-7-H-K	File not available for this product
08	PV08-7-H-K	File not available for this product
09	PV09-7-H-K	File not available for this product
10	PV10-7-H-K	File not available for this product
11	PV11-7-H-K	File not available for this product