

# PVS\_\_-7-L12,2



## GENERAL INFORMATION

pitch	7 mm
Height	12.2 mm
Depth	2.8 mm
Dimensional class	Bassa
Wire section	-
Clamp opening size	-
Wire stripping	-
Operating temperature	-40 ÷ +130 °C

## ELECTRICAL CHARACTERISTICS

Current	8 A
Voltage	400 V
impulse voltage	6 kV

## MECHANICAL CHARACTERISTICS

Screw	-
Recommended torque	-

## APPROVALS DATA



Current	-	-	-
Voltage	-	-	-
Wire section	-	-	-
Torque	-	-	-
FILE	-	-	-

## MATERIALS

Housing	PA - UL 94 V0
Screw	-
Clamp	-
Terminal	Tin-plated copper alloy
SCIP Number	e7871ea5-2cf8-4f17-b626-38a85b04faba

## COLOURS

Standard

On request



<b>POLES</b>	<b>NAME</b>	<b>3D FILE</b>
02	PVS02-7-L12,2	File not available for this product
03	PVS03-7-L12,2	File not available for this product
04	PVS04-7-L12,2	File not available for this product
05	PVS05-7-L12,2	File not available for this product
06	PVS06-7-L12,2	File not available for this product
07	PVS07-7-L12,2	File not available for this product
08	PVS08-7-L12,2	File not available for this product
09	PVS09-7-L12,2	File not available for this product
10	PVS10-7-L12,2	File not available for this product
11	PVS11-7-L12,2	File not available for this product
12	PVS12-7-L12,2	File not available for this product