
MG1__-5-V







GENERAL INFORMATION

pitch 5 mm Height 13.2 mm Depth 15.4 mm **Dimensional class** Bassa 2.5 mm² / 14 AWG Wire section 2.45 x 2.45 mm Clamp opening size Wire stripping max 9 mm **Operating temperature** -40 ÷ +130 °C

ELECTRICAL CHARACTERISTICS

 Current
 24 A

 Voltage
 450 V

 Test Voltage
 2 kVrms/60s

MECHANICAL CHARACTERISTICS

Screw

Recommended torque APPROVALS DATA







UL 1059

 Current
 17 A factory / 17 A field

 Voltage
 300 V

 Wire section
 12 ÷ 30 AWG

 Torque

 FILE
 E178356

MATERIALS

HousingPA - UL 94 VOScrew-SpringSpring steelTerminalTin-plated copper alloy

COLOURS

Standard On request















POLES	NAME	3D FILE
01	MG101-5-V	File not available for this product
02	MG102-5-V	File not available for this product
03	MG103-5-V	File not available for this product
04	MG104-5-V	File not available for this product
05	MG105-5-V	File not available for this product
06	MG106-5-V	File not available for this product
07	MG107-5-V	File not available for this product
08	MG108-5-V	File not available for this product
09	MG109-5-V	File not available for this product
10	MG110-5-V	File not available for this product
11	MG111-5-V	File not available for this product
12	MG112-5-V	File not available for this product
13	MG113-5-V	File not available for this product
14	MG114-5-V	File not available for this product
15	MG115-5-V	File not available for this product
16	MG116-5-V	File not available for this product
17	MG117-5-V	File not available for this product
18	MG118-5-V	File not available for this product
19	MG119-5-V	File not available for this product
20	MG120-5-V	File not available for this product
21	MG121-5-V	File not available for this product
22	MG122-5-V	File not available for this product
23	MG123-5-V	File not available for this product