

PV -5-H-P







GENERAL INFORMATION

pitch 5 mm
Height 8.5 mm
Depth 12.2 mm
Dimensional class Media
Wire section -

Clamp opening size Wire stripping

Operating temperature

The state of the s

ELECTRICAL CHARACTERISTICS

 Current
 16 A

 Voltage
 250 V

 Test Voltage
 4 kVrms/60s

MECHANICAL CHARACTERISTICS

Screw

Recommended torque APPROVALS DATA







-40 ÷ +130 °C

	EN 61984	EN 61984	UL 1059
Current	16 A	12 A	16 A factory / 16 A field
Voltage	250 V	250 V	300 V
Wire section	-	-	-
Torque	-	-	-
FILE	CA02.04178	40005779	E178356

MATERIALS

Housing PA - UL 94 V0
Screw Clamp -

Terminal Tin-plated copper alloy

COLOURS

Standard On request

GN
BK
BL
RD
YL
OG

POLES	NAME	3D FILE
02	PV02-5-H-P	File available
03	PV03-5-H-P	File available
04	PV04-5-H-P	File available
05	PV05-5-H-P	File available
06	PV06-5-H-P	File available
07	PV07-5-H-P	File available
08	PV08-5-H-P	File available
09	PV09-5-H-P	File available
10	PV10-5-H-P	File available
11	PV11-5-H-P	File available
12	PV12-5-H-P	File available
13	PV13-5-H-P	File not available for this product
14	PV14-5-H-P	File not available for this product
15	PV15-5-H-P	File not available for this product
16	PV16-5-H-P	File available
17	PV17-5-H-P	File not available for this product
18	PV18-5-H-P	File not available for this product
19	PV19-5-H-P	File not available for this product
20	PV20-5-H-P	File not available for this product
21	PV21-5-H-P	File not available for this product
22	PV22-5-H-P	File not available for this product
23	PV23-5-H-P	File not available for this product
24	PV24-5-H-P	File not available for this product