

# SF\_\_-15-P



## GENERAL INFORMATION

pitch	15 mm
Height	15.5 mm
Depth	19.2 mm
Dimensional class	Media
Wire section	2.5 mm <sup>2</sup> / 14 AWG
Clamp opening size	2.8 x 2.9 mm
Wire stripping	max 8 mm
Operating temperature	-40 ÷ +130 °C

## ELECTRICAL CHARACTERISTICS

Current	16 A
Voltage	1000 V
impulse voltage	6 kV

## MECHANICAL CHARACTERISTICS

Screw	M3
Recommended torque	0.5÷0.55 Nm / 4.5÷4.9 in.lbs

## APPROVALS DATA



			<b>UL 1059</b>
Current	-	-	22 A factory / 20 A field
Voltage	-	-	600 V
Wire section	-	-	12 AWG
Torque	-	-	4.5 Lb-in
FILE	-	-	E178356

## MATERIALS

Housing	PA - UL 94 V0
Screw	Galvanized steel
Clamp	Nickel-plated copper alloy
Terminal	Nickel-plated copper alloy
SCIP Number	e27c55ac-423d-4d46-808e-20cdb05c39b8

## COLOURS

Standard

On request

**GN**

**GY**

**BK**

**BL**

**RD**

**YL**

**OG**

<b>POLES</b>	<b>NAME</b>	<b>3D FILE</b>
02	SF02-15-P	File not available for this product
03	SF03-15-P	File not available for this product
04	SF04-15-P	File not available for this product
05	SF05-15-P	File not available for this product
06	SF06-15-P	File not available for this product
07	SF07-15-P	File not available for this product
08	SF08-15-P	File not available for this product