

# SHM\_\_-5,08-M



### GENERAL INFORMATION

pitch	5,08 mm
Height	15 mm
Depth	23.7 mm
Dimensional class	Media
Wire section	2.5 mm <sup>2</sup> / 14 AWG
Clamp opening size	-
Wire stripping	max 10 mm
Operating temperature	-40 ÷ +130 °C

### ELECTRICAL CHARACTERISTICS

Current	12 A
Voltage	250 V
Test Voltage	4 kVrms/60s

### MECHANICAL CHARACTERISTICS

Screw	-
Recommended torque	-

### APPROVALS DATA



			<b>UL 1059</b>
Current	-	-	16 A factory / 16 A field
Voltage	-	-	300 V
Wire section	-	-	12 ÷ 30 AWG
Torque	-	-	-
FILE	-	-	E178356

### MATERIALS

Housing	PA - UL 94 V0
Screw	-
Clamp	-
Terminal	Tin-plated copper alloy

### COLOURS

Standard

On request

**GN**

**GY**

**BK**

**BL**

**RD**

**YL**

**OG**

<b>POLES</b>	<b>NAME</b>	<b>3D FILE</b>
02	SHM02-5,08-M	File not available for this product
03	SHM03-5,08-M	File not available for this product